

Specification

Nominal Basket Diameter	15", 381mm
Nominal Impedance*	8 ohms
Power Rating**	
Watts	450W
Music Program	900W
Resonance	44Hz
Usable Frequency Range***	40Hz-1.5kHz
Sensitivity	98.4
Magnet Weight	11 oz.
Gap Height	0.365", 9.27mm
Voice Coil Diameter	3", 76.2mm

Thiele & Small Parameters

Resonant Frequency (fs)	44Hz
DC Resistance (Re)	5.5
Coil Inductance (Le)	0.93mH
Mechanical Q (Qms)	8.97
Electromagnetic Q (Qes)	.48
Total Q (Qts)	.46
Compliance Equivalent Volume (Vas)	150.9 liters / 5.3 cu.ft.
Peak Diaphragm Displacement Volume (Vd)	846cc
Mechanical Compliance of Suspension (Cms)	0.14mm/N
BL Product (BL)	17.0 T-M
Diaphragm Mass inc. Airload (Mms)	93.4 grams
Efficiency Bandwidth Product (EBP)	90
Maximum Linear Excursion (Xmax)	9.6mm
Surface Area of Cone (Sd)	881.1 cm ²
Maximum Mechanical Limit (Xlim)	17.0mm

Mounting Information

Recommended Enclosure Volume	
Sealed	N/A
Vented	99-195 liters/3.5-6.9 cu.ft.
Driver Volume Displaced	156.4 cu.in. / 2.56 liters
Overall Diameter	15.32", 389.1mm
Baffle Hole Diameter	14.03", 356.4mm
Front Sealing Gasket	Fitted as standard
Rear Sealing Gasket	Fitted as standard
Mounting Holes Diameter	0.28", 7.1mm
Mounting Holes B.C.D.	14.56", 369.8mm
Depth	7.25", 184.2mm
Net Weight	8.6 lbs., 3.9 kg
Shipping Weight	10.7 lbs., 4.9 kg


Materials of Construction

Copper voice coil
 Kapton
 Neodymium magnet
 Vented core
 Die-cast aluminum basket/heatsink
 Treated Paper Cone
 Cloth cone edge
 Treated paper dust cap



KAPPALITE™ 3015LF Neodymium Series

Recommended for professional audio and bass in a vented enclosure.



* Please inquire about alternative impedances.

** Multiple units exceed published rating evaluated under EIA 426A noise source and test standard while in a free-air, non-temperature controlled environment.

*** The average output across the usable frequency range when applying 1W/1M into the nominal impedance. Ie: 2.83V/8ohms, 4V/16ohms.

Eminence response curves are measured under the following conditions: All speakers are tested at 1w/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2ft. X 2ft. baffle is built into the wall with the speaker mounted flush against a steel ring for minimum diffraction | Hafler P1500 Trans-Nova amplifier | 2700 cu.ft. chamber with fiberglass on all six surfaces (three with custom-made wedges)